

ART 700

700W DAB/DAB+ COMPACT TRANSMITTER



- BROADBAND DOHERTY Very high efficiency
- Compact, flexible and light
- Linear & non-linear adaptive precorrection
- Front panel display, SNMP & Web GUI controls
- Magnetic cover with removable air filter
- Integrated GPS/Glonass receiver for SFN operation as option
- Option for modular configuration with single or dual exciter



ART SERIES DAB TRANSMITTERS



- Hot-pluggable power supply units
- Partial redundant power supply
- Easy plug fans

GENERAL SPECIFICATION

Output frequency range Frequency agile in the VHF BIII 174 to 230MHz

Output Power (before output filter) 700Wrms (tol. +0/-0,5dB)

Output connector DIN 7-16 female

DAB Modulator DAB, DAB+ Mode I, II, III and IV. MFN and SFN operation

Fully compliant with standard TS 102 428

Inputs 2x EDI - Ethernet RJ45 (option)

 $2x ETI - BNC 75 \Omega$

Digital Adaptive PrecorrectionLinear and non-linear with PAPR and clipping protection

MER ≥33dB

Housing Rack Drawer 19" 3U

Weight <30Kg

Typ. efficiency ≥40%

AC input voltage/ frequency 90 to 264Vac 47/63Hz single phase (full output power from 176 to 264Vac)



All specifications contained in this document may be changed without prior notice